

Here are a few reasons
you should use
KDF® Process Media
in your POE systems: chlorine,
hydrogen sulfide, heavy metals
and microorganisms

Need more reasons?

KDF Process Media enhance the performance of activated carbon and silver-impregnated media, extend the service life of RO membranes and ion exchange resins, and reduce your paperwork.

**And let's not forget
satisfied customers.**

KDF Process Media are high-purity copper-zinc granules that use redox (the exchange of electrons) to remove chlorine, hydrogen sulfide, water-soluble heavy metals and microorganisms from water. Effective? This highly-effective, patented alloy removes more than 95% of the free chlorine before it reaches your carbon bed so your carbon can concentrate on removing organics, thus extending its useful service life by up to 15 times. You'll discover yourself using less carbon and treating yourself to fewer carbon change-outs, smaller carbon beds and then smaller filters.

With long-lasting, recyclable **KDF Process Media**, RO membranes and ion exchange resins will last longer. You'll make fewer service calls. Next time you see your customers, they'll be smiling—not snarling.

KDF Process Media are also more effective than silver-impregnated media. Silver has to be registered with the EPA, but this unique non-toxic alloy is classified as a "pesticidal device" that doesn't require registration. Now you'll run into less red tape, do less paperwork, and have fewer headaches.

Need more reasons to try **KDF Process Media**? More information, FREE samples, independent laboratory test results and/or technical assistance are only a click away at www.kdfft.com.



FLUID TREATMENT, INC.
Solutions for economical clean water™

1500 KDF Drive
Three Rivers, Michigan 49093-9287
Toll-free: 1-800-437-2745
Phone: 1-616-273-3300 • Fax: 1-616-273-4400
E-mail: kdf1@att.net • Web: www.kdfft.com



KDF® process media product specifications for point-of-entry (POE) applications

KDF 55 Process Medium Specifications

Applications: Chlorine, Heavy Metal Removal and Bacteria.

Medium compositionatomized high purity copper/zinc alloy
 Color.....golden
 Physical formgranular
 Screen size (U.S. mesh)-10 + 100
 Particle size range0.149 mm to 2.00 mm
 Apparent density2.4-2.9 g/cc (171 lbs./cu.ft.)
 Turbidity<20 ntu
 Skid.....48-1/3 cu. ft. drums (2,736 lbs.)
 Odor and tastesnone

Recommended Operating Conditions (use 3-cycle valve):

Service flow15 gpm/sq. ft.
 Backwash for 10 min. @30 gpm/sq. ft.
 Purge/rinse for 3 min. @maximum
 Bed expansion, backwash10 to 15%
 Free board20%
 Minimum bed depth (6" dia.).....10 inches
 pH range: drinking water6.5 to 8.5
 Water temperature, influent35° to 212°F.

KDF 85 Process Medium Specifications

Applications: Iron and Hydrogen Sulfide

Medium compositionatomized high purity copper/zinc alloy
 Colorreddish brown
 Physical formgranular
 Screen size (U.S. mesh)-10 + 100
 Particle size range0.149 mm to 2.00 mm
 Apparent density2.2-2.7 g/cc (171 lbs./cu. ft.)
 Turbidity<20 ntu
 Skid.....48-1/3 cu. ft. drums (2,736 lbs.)
 Odor and tastesnone

Recommended Operating Conditions (use 3-cycle valve):

Service flow15 gpm/sq. ft.
 Backwash for 10 min. @30 gpm/sq. ft.
 Purge/rinse for 3 min. @maximum
 Bed expansion, backwash10 to 15%
 Free board20%
 Minimum bed depth (6" dia.).....10 inches
 pH range: drinking water6.5 to 8.5
 Water temperature, influent35° to 212°F.

The data included herein are based on outside laboratory tests. We believe the data are reliable, but recommend that users test performance on their own equipment. When using KDF media, proper backwash procedures should be applied.

Maximum Service Flow (gpm)	Tank Size Diameter (inches)	Backwash Valve Required	Distributor	Minimum Backwash Rate (gpm)	Pipe Size Diameter (inches)	KDF Process Media			
						Bed Depth (inches)	Weight (lbs)	Volume (cu. ft.)	No. of Drums
3	6x35	3-cycle	Felt or fine slotted	6	0.75	10	28.5	0.16	0.5
4	7x35			8	0.75	11	42.8	0.25	0.75
5.5	8x40			10	0.75	12	57.0	0.33	1.0
6	9x42			12	0.75	13	85.5	0.50	1.5
8	10x44			16	0.75	14	114.0	0.66	2.0
11	12x48			22	1	16	171.0	1.04	3.0
15	14x65			30	1	18	285.0	1.60	5.0
20	16x65			40	1.5	20	399.0	2.33	7.0
25	18x65			50	1.75	22	627.0	3.50	11.0
36	21x65			Diaphragm nest	Hub and lateral	72	2	24	855.0
45	24x72	90	2			25	1140.0	6.50	20.0
72	30x72	144	2.5			25	1767.0	10.25	31.0
100	36x72	200	2.5			25	2565.0	14.75	45.0
144	42x72	288	3			25	3420.0	20.00	60.0
188	48x72	376	4			25	4446.0	26.00	78.0
324	63x86	648	5			25	7695.0	45.00	135.0



FLUID TREATMENT, INC.
 Solutions for economical clean water™

1500 KDF Drive
 Three Rivers, Michigan 49093-9287
 Toll-free: 1-800-437-2745
 Phone: 1-616-273-3300 • Fax: 1-616-273-4400
 E-mail: kdf1@att.net • Web: www.kdff.com

