

*KDF Process Media* are high-purity copper-zinc granules that use redox (the exchange of electrons) to remove chlorine, hydrogen sulfide, water-soluble heavy metals and microorganisms from water. Effective? This highly-effective, patented alloy removes more than 95% of the free chlorine before it reaches your carbon bed so your carbon can concentrate on removing organics, thus extending its useful service life by up to 15 times. You'll discover yourself using less carbon and treating yourself to fewer carbon change-outs, smaller carbon beds and then smaller filters.

With long-lasting, recyclable *KDF Process Media*, RO membranes and ion exchange resins will last longer. You'll make fewer service calls. Next time you see your customers, they'll be smiling—not snarling.

*KDF Process Media* are also more effective than silver-impregnated media. Silver has to be registered with the EPA, but this unique non-toxic alloy is classified as a "pesticidal device" that doesn't require registration. Now you'll run into less red tape, do less paperwork, and have fewer headaches.

Need more reasons to try *KDF Process Media*? More information, FREE samples, independent laboratory test results and/or technical assistance are only a click away at [www.kdfft.com](http://www.kdfft.com).

®

## FLUID TREATMENT, INC.

Solutions for economical clean water™

1500 KDF Drive  
Three Rivers, Michigan 49093-9287  
Toll-free: 1-800-437-2745



## KDF® process media product specifications for point-of-entry (POE) applications

### KDF 55 Process Medium Specifications

Applications: Chlorine, Heavy Metal Removal and Bacteria.

Medium composition .....atomized high purity copper/zinc alloy  
 Color.....golden  
 Physical form .....granular  
 Screen size (U.S. mesh) .....-10 + 100  
 Particle size range .....0.149 mm to 2.00 mm  
 Apparent density .....2.4-2.9 g/cc (171 lbs./cu.ft.)  
 Turbidity .....<20 ntu  
 Skid.....48-1/3 cu. ft. drums (2,736 lbs.)  
 Odor and tastes .....none

#### Recommended Operating Conditions (use 3-cycle valve):

Service flow .....15 gpm/sq. ft.  
 Backwash for 10 min. @ .....30 gpm/sq. ft.  
 Purge/rinse for 3 min. @ .....maximum  
 Bed expansion, backwash .....10 to 15%  
 Free board .....20%  
 Minimum bed depth (6" dia.).....10 inches  
 pH range: drinking water .....6.5 to 8.5  
 Water temperature, influent .....35° to 212°F.

### KDF 85 Process Medium Specifications

Applications: Iron and Hydrogen Sulfide

Medium composition .....atomized high purity copper/zinc alloy  
 Color .....reddish brown  
 Physical form .....granular  
 Screen size (U.S. mesh) .....-10 + 100  
 Particle size range .....0.149 mm to 2.00 mm  
 Apparent density .....2.2-2.7 g/cc (171 lbs./cu. ft.)  
 Turbidity .....<20 ntu  
 Skid.....48-1/3 cu. ft. drums (2,736 lbs.)  
 Odor and tastes .....none

#### Recommended Operating Conditions (use 3-cycle valve):

Service flow .....15 gpm/sq. ft.  
 Backwash for 10 min. @ .....30 gpm/sq. ft.  
 Purge/rinse for 3 min. @ .....maximum  
 Bed expansion, backwash .....10 to 15%  
 Free board .....20%  
 Minimum bed depth (6" dia.).....10 inches  
 pH range: drinking water .....6.5 to 8.5  
 Water temperature, influent .....35° to 212°F.

*The data included herein are based on outside laboratory tests. We believe the data are reliable, but recommend that users test performance on their own equipment. When using KDF media, proper backwash procedures should be applied.*

Maximum Service Flow (gpm)	Tank Size Diameter (inches)	Backwash Valve Required	Distributor	Minimum Backwash Rate (gpm)	Pipe Size Diameter (inches)	KDF Process Media			
						Bed Depth (inches)	Weight (lbs)	Volume (cu. ft.)	No. of Drums
3	6x35	3-cycle	Felt or fine slotted	6	0.75	10	28.5	0.16	0.5
4	7x35			8	0.75	11	42.8	0.25	0.75
5.5	8x40			10	0.75	12	57.0	0.33	1.0
6	9x42			12	0.75	13	85.5	0.50	1.5
8	10x44			16	0.75	14	114.0	0.66	2.0
11	12x48			22	1	16	171.0	1.04	3.0
15	14x65			30	1	18	285.0	1.60	5.0
20	16x65			40	1.5	20	399.0	2.33	7.0
25	18x65			50	1.75	22	627.0	3.50	11.0
36	21x65			Diaphragm nest	Hub and lateral	72	2	24	855.0
45	24x72	90	2			25	1140.0	6.50	20.0
72	30x72	144	2.5			25	1767.0	10.25	31.0
100	36x72	200	2.5			25	2565.0	14.75	45.0
144	42x72	288	3			25	3420.0	20.00	60.0
188	48x72	376	4			25	4446.0	26.00	78.0
324	63x86	648	5			25	7695.0	45.00	135.0



**FLUID TREATMENT, INC.**  
 Solutions for economical clean water™

1500 KDF Drive  
 Three Rivers, Michigan 49093-9287  
 Toll-free: 1-800-437-2745  
 Phone: 1-616-273-3300 • Fax: 1-616-273-4400  
 E-mail: kdf1@att.net • Web: www.kdff.com

